

Technical product information

Fabric tape, silver grey, matte, PE-coated, extremely permanent adhesive

Material code: MR-Geweberonden

Status: Aug-26

Upper

PE-coated fabric made of PET/cellulose fabric (70 mesh)

Feature	Value	Unit
Elongation at break	approx. 15	%
Tensile strength	approx. 95	N/15 mm

Adhesive

Extremely permanent pressure-sensitive adhesive

Feature	Value
Initial adhesive strength	very strong
Final adhesive strength	very strong

Liner

PE Extruded Fabric

Adhesive bond

Feature	Value	Unit
Thickness	approx. 300	µm
Application temperature	-35 to 80	°C

Shelf life

The material should be stored at a temperature of 20 ± 5 °C and a relative humidity of $45 \pm 5\%$ dry, protected from light and in the original packaging. Moisture, heat and direct sunlight should be avoided. If stored properly, the shelf life is 1 year from the date of manufacture.

The information available describes the product in its essential technical characteristics. They are for general guidance and do not constitute a guarantee or assurance of specific characteristics. The suitability of the material for the respective application must be checked by the user on his own responsibility. Labelident does not accept any liability beyond the obligations regulated by law or specified in the general terms and conditions of sale. Technical changes in the context of product development are reserved. Labelident is not the manufacturer of the raw material described.