Technical product information

Parcel tape, brown/transparent, quietly unwinding

Status: Okt-26

Adhesive

Water-based acrylate-based pressure-sensitive adhesive

Feature	Value
Adhesion to steel	strong
Tensile strength	medium strong
Holding force	strong
Elongation	strong

Liner

Transparent/Brown BOPP Film – Biaxially Oriented Polypropylene Film

Adhesive bond

Feature	Value	Unit
Thickness	approx. 48	µm
Application temperature	0 to 60	°C

Product features

The tape is characterized by quiet unwinding without blistering. It offers strong initial adhesion and ensures long-lasting adhesive strength. In addition, the product is suitable for applications where quiet processing and reliable adhesion are required.

Shelf life

The material should be stored at a temperature of 15 – 30 °C and a relative humidity < 70% dry, protected from light and in the original packaging. Moisture, heat and direct sunlight should be avoided. If stored properly, the shelf life is 1 year from the date of manufacture.

The information provided describes the product in its essential technical characteristics. It is for general guidance purposes and does not constitute a guarantee or assurance of specific properties. The suitability of the material for the respective purpose is to be checked by the user on his own responsibility. Labelident assumes no liability beyond the obligations regulated by law or specified in the general terms and conditions of sale. Technical changes in the context of product development are reserved. Labelident is not the manufacturer of the raw material described.

Labelident GmbH | A company of the Klaus Kroschke Group | Headquarters: Parisstraße 5, 97424 Schweinfurt, Germany
Web: www.labelident.com | E-mail: info@labelident.de | Phone: +49 9721 793 98 11