

# Technical product information

Thermal paper 60 g/m<sup>2</sup>, white, matt

Material code: TR

Status: Apr-26

## Material

White thermal paper made from 90% pulp, 10% BPA-free thermal coating

Feature	Value	Unit
Basis weight	approx. 60	g/m <sup>2</sup>
Thickness	ca. 92 - 96	µm
Tensile strength (MD)	≥ 2.0	kN/m
Tear Resistance (CD)	≥ 150	mN
Image retention rate	≥ 90	%

### Thermal Printing Properties - Static

Feature	Value
Density after heating at 70 °C	≤ 0.25
Saturation Image Density	≥ 1.05

### Thermal Printing Properties - Dynamic

Feature	Value	Unit
Image sensitivity	≤ 10	mJ/mm <sup>2</sup>
Saturation Image Density	≥ 1.05	

## Shelf life

The material should be stored at a temperature of 5 - 30 °C and a relative humidity below 50% dry, protected from light and in the original packaging. Moisture, heat and direct sunlight should be avoided. When stored properly, the shelf life is up to 10 years from the date of manufacture and the printed image remains legible for up to 10 years.

## Conformities

The material used is made of BPA-free thermal paper and is recyclable. It thus meets the highest standards in safety and environmental friendliness.

The information available describes the product in its essential technical characteristics. They are for general guidance and do not constitute a guarantee or assurance of specific characteristics. The suitability of the material for the respective application must be checked by the user on his own responsibility. Labelident does not accept any liability beyond the obligations regulated by law or specified in the general terms and conditions of sale. Technical changes in the context of product development are reserved. Labelident is not the manufacturer of the raw material described.