

Technical product information

Polypropylene, white, matt, coated, permanent adhesive

Material code: MR-F-INK

Status: Feb-26

Upper

White, matt inkjet polypropylene

Feature	Value	Unit
Basis weight	approx. 66	g/m ²
Thickness	approx. 97	µm

Adhesive

Permanent acrylate-based pressure-sensitive adhesive

Feature	Value
Initial adhesive strength	strong
Final adhesive strength	medium

Liner

White glassine paper

Feature	Value	Unit
Basis weight	approx. 80	g/m ²
Thickness	approx. 53	µm

Adhesive bond

Feature	Value	Unit
Minimum bonding temperature	10	°C
Application temperature	-10 to 65	°C

Shelf life

The material should be stored at a temperature of 23 ± 2 °C and a relative humidity of $50 \pm 5\%$ dry, protected from light and in its original packaging. Moisture, heat and direct sunlight should be avoided. If stored properly, the shelf life is 1 year from the date of manufacture.

The information available describes the product in its essential technical characteristics. They are for general guidance and do not constitute a guarantee or assurance of specific characteristics. The suitability of the material for the respective application must be checked by the user on his own responsibility. Labelident does not accept any liability beyond the obligations regulated by law or specified in the general terms and conditions of sale. Technical changes in the context of product development are reserved. Labelident is not the manufacturer of the raw material described.