

Technical product information

Polyester, white, glossy, coated, permanent adhesive

Material code: MR-A-GL8

Status: Feb-26



Upper

White, glossy polyester film

Feature	Value	Unit
Thickness	approx. 50	µm

Adhesive

Permanent acrylate-based pressure-sensitive adhesive

Feature	Value
Final adhesive strength	very strong
Shear strength	very strong

Liner

White, supercalendered glassine paper

Feature	Value	Unit
Thickness	approx. 56	µm

Adhesive bond

Feature	Value	Unit
Thickness	approx. 126	µm
Minimum bonding temperature	2	°C
Application temperature	-40 to 150	°C

The information available describes the product in its essential technical characteristics. They are for general guidance and do not constitute a guarantee or assurance of specific characteristics. The suitability of the material for the respective application must be checked by the user on his own responsibility. Labelident does not accept any liability beyond the obligations regulated by law or specified in the general terms and conditions of sale. Technical changes in the context of product development are reserved. Labelident is not the manufacturer of the raw material described.

Technical product information

Polyester, white, glossy, coated, permanent adhesive

Material code: MR-A-GL8

Status: Feb-26



Shelf life

The material should be stored at a temperature of 21 °C and a relative humidity of 50% dry, protected from light and in the original packaging. Moisture, heat and direct sunlight should be avoided. When stored properly, the shelf life is 2 years from the date of manufacture.

Conformities

This product is UL certified for indoor and outdoor use with occasional exposure to lubricating oil and water, file number MH 16635.

The information available describes the product in its essential technical characteristics. They are for general guidance and do not constitute a guarantee or assurance of specific characteristics. The suitability of the material for the respective application must be checked by the user on his own responsibility. Labelident does not accept any liability beyond the obligations regulated by law or specified in the general terms and conditions of sale. Technical changes in the context of product development are reserved. Labelident is not the manufacturer of the raw material described.