

Technical product information

Paper, white, matte, uncoated, permanently adhesive

Material code: MB-PP

Status: Sep-26

Upper

Matte white, wood-free paper for clean printing results on laser and photocopiers

Feature	Value	Unit	Standard
Basis weight	approx. 70	g/m ²	ISO 536
Thickness	approx. 88	µm	ISO 534

Adhesive

Permanent acrylate-based pressure-sensitive adhesive

Feature	Value
Initial adhesive strength	strong
Final adhesive strength	strong

Liner

White, smooth and tear-resistant kraft paper

Feature	Value	Unit	Standard
Basis weight	approx. 58	g/m ²	ISO 536
Thickness	approx. 58	µm	ISO 534

Adhesive bond

Feature	Value	Unit
Thickness	approx. 165	µm
Minimum bonding temperature	5	°C
Application temperature	-25 to 70	°C

Shelf life

The material should be stored at a temperature of 15 - 30 °C and a relative humidity of 50 ± 5% dry, protected from light and in the original packaging. Moisture, heat and direct sunlight should be avoided. If stored properly, the shelf life is 1 year from the date of manufacture.

The information provided describes the product in its essential technical characteristics. It is for general guidance purposes and does not constitute a guarantee or assurance of specific properties. The suitability of the material for the respective purpose is to be checked by the user on his own responsibility. Labelident assumes no liability beyond the obligations regulated by law or specified in the general terms and conditions of sale. Technical changes in the context of product development are reserved. Labelident is not the manufacturer of the raw material described.