

## Product Construction Sheet

THERMLfilm® ADVANTAGE Extreme Satin Silver (Roll-Liner)

PET-DUA2-9U09S/36



### GENERAL DESCRIPTION:

A top-coated satin silver coloured metalized polyester film, coated with a permanent high tack acrylic adhesive, backed with a glassine liner.

PRODUCT DATA		VALUE	TEST METHOD
<b>PHYSICAL PROPERTIES</b>			
Thickness (micron)	Film	50 +/- 10 %	ASTM D 3652
	Adhesive	35-38 +/- 3	
	Liner	56 +/- 10%	
Dimensional Stability (%)	Machine Direction	No shrinkage observed	On AL panel at 70°C for 24 hr.

### ADHESION PROPERTIES\*\*

Adhesion from (N/25mm)	Average	
Stainless Steel	26	FTM 1 (72 hr dwell time)
Glass	26	
Acrylic	28	
PP	30	
Expected Shear (Hours)	100	FTM 8
Tack (gm/sq cm)	948	ASTM D 2979

### UL RECOGNITION:

This product is UL recognized for indoor/outdoor use with occasional exposure to lubricating oil and water. For further information, please reference FLEXcon's UL file No MH16635 (N) or contact your FLEXcon Representative.

### \*\*\* For guidance only

This data is based on limited test results on adhesive coat weight of: 36 micron micron. Due to the custom nature of this product, not to be used for setting specifications.

EXPECTED EXTERIOR LIFE	2 years
SERVICE TEMPERATURE RANGE	-40°C to 150°C
MINIMUM APPLICATION TEMPERATURE	10°C
STORAGE STABILITY	Two years stored at 21°C and 50% RH

\* THERMLfilm® is a trademark of FLEXcon Company Inc

09/08/2022

S 1395

### Product Performance and Suitability

All of the descriptive information, the typical performance data, and recommendations for the use of FLEXcon products shall be used only as a guide and do not reflect the specification or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by FLEXcon. All purchasers of FLEXcon products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of FLEXcon is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.